

Document
Number:Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046P.O Box 7182, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
RooihuiskraalTel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za**TDS 133****SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with ISO 9001 & 14001)***VISCOL ANTIFREEZE NF****Description & Characteristics:**

Viscol Antifreeze NF is a high quality product containing aliphatic carboxylate anti-corrosion additives. The NF version is nitrite and silicate free. It reduces the freezing point of the cooling water and increases the boiling point. The anti-corrosion additives give protection to Aluminium, copper, cast iron and other metals used in cooling systems. Heat transfer is excellent compared to silicate containing coolants. Can be used in all heavy duty engines using emission control including EGR, DPF and SCR technology. Caution: Some OEM's require the use of nitrate in heavy duty engine applications.

Specifications:

ASTM D3306, ASTM D4985, SAE J 1034, BS 6480 (1992), AFNOR NF R15-601 and TSE 3582

Physical Properties:

VISCOL ANTIFREEZE	
Relative Density @ 15°C	1,112
Reserve Alkalinity ml 0,1, NHCL	5.6
Freezing 50% Point(°C)	-40
Freezing 33% Point (°C)	-20
Boiling Point(°C)	169,0

Mixture Ratios:

50% Dilution with deionized water: -34 deg. C protection*. Service life of 1million Km's/12000 hours/6 years with no extender needed. Colour pale yellow/green.

*These temperatures based on using a 103KPA radiator cap.

Packaging:

210 litre drums
20 litre drums

Page:	1/2	Date:	1/10/2016	Supercedes:	
SOP ref:	(Rev. 02)	Compiled by:	Alex Hime	Checked by:	Authorised by:



Document
Number:

Viscol cc
Reg No: 1987/028096/23
Vat Reg: 4380103046

P.O Box 7182, Centurion, 0046
130 Sarelbaard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661 9888
Fax: (012) 661 9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

TDS 133

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with ISO 9001 & 14001)

Performance Standards:

ASTM D3306
ASTM D 4985
SAE J 1034
BS 6580 (1992)
AFNOR NF R15-601*
FFV Heft R443
CUNA NC 956-16
UNE 26361-88
JIS K 2234*
NATO S 759

(* with the exception of reverse alkalinity)

It also meets the performance requirements of the following OEM specifications:

Chrysler MS 9176
Cummins 85T8-2 & 90T8-4
Ford ESE M97B49-A, WSS-M97B44-D & ESD M97 B49-A
GM 1899 M, US 6277 M & OPEL GM QL130100
John Deere H 24 B1 & C1
Leyland Trucks LTS 22 AF 10
Mack 248, 324 (SNF) & B&W D 36 5600
Mercedes MB 325.3
Renault 41-01-001
VAG TL 774F
Volvo

Packaging:

210 litre Plastic drums
20 litre Plastic drums

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 2/2	Date: 1/10/2016	Supercedes:	
SOP ref: (Rev. 02)	Compiled by: Alex Hime	Checked by:	Authorised by: