

**Specialists in Industrial & Automotive Oil**

Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document Name:

TDS002**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with SABS ISO 9001 & 14001)***BRICKLITE****Product Description:**

A low viscosity mineral lubricating oil containing blends of light process oils and medium flash kerosenes. A formulation exclusively manufactured for the clay brick industry for extrusion of bricks. Bricklite has a dual function and may also be used in a fuel firing system.

Gross Calorific Value @ 15 °C, KJ/kg 46050
Viscosity, mm²/s @ 40 °C 4,7

Product Application:

1. Used in the process of clay brick extrusion.
2. Used in a fuel firing system.
3. Simple handling equipment as a result of low viscosity.
4. Easy atomisation and control.

Product Packaging:

210 litre and bulk

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

| | | | |
|-----------------|---------------------------|--------------------|----------------|
| Page: 1/1 | Date: 26/06/2003 | Supercedes: New | |
| SOP ref: New | Compiled by: Alex Hime | Checked by: | Authorised by: |