

**Specialists in Industrial & Automotive Oil**

Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@jafrika.com
Website: www.viscol.co.za

Document
Number:

TDS004

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with SABS ISO 9001 & 14001)

CASTRIP 950

Description and Characteristics

Castrip 950 is a ready to use mould release oil for the production of railway sleepers, lintels and concrete slabs. The additives used in Castrip 950 enhance the releasing properties, protect the moulds from staining and provides an extremely clean release after curing.

Physical Characteristics

Viscosity at 40°C cST	6
Specific Gravity at 20°C kg/1	0.85
Open cup flash point ASTM D92°C	65

Benefits

Extremely good releasing properties.
Non staining of pallets.
Good coverage.
Ready to use.

Application

Can be applied by swab, brush or spray.

Specifications

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

Page: 1/1	Date: 30/10/2004	Supersedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: