



Specialists in Industrial & Automotive Oil

Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document Number:

TDS010

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with SABS ISO 9001 & 14001)

MULTISTRIP A2

Description

A low viscosity petroleum blend incorporating releasing additives for excellent off-shutter finishes. All-round and general purpose effective shutter and mould release agent. Non-staining and colourless.

Application

1. Apply one coat by spray, roller or brush.
2. Timber, steel, fibreglass and concrete moulds.
3. 25 m² coverage per litre.
4. Does not affect plaster.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use. The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 31/04/2002	Supersedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: