



**Specialists in Industrial & Automotive Oil**

Viscol cc  
Reg No: 1987/028096/23  
Vat Reg : 4380103046

P.O. Box: 7182, Centurion, 0046  
130 Sarel Baard Crescent  
Gateway Industrial Park  
Rooihuiskraal

Tel: (012) 661-9888  
Fax: (012) 661-9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za

Document Number:

**TDS011**

**SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with SABS ISO 9001 & 14001)*

**VISCOL PIPEASE I**

**Product Description:**

A low viscosity kerosene based mould-releasing agent initially formulated for the use in moulding of spun cement pipes. A clear coloured formulation of fatty acids; tackifiers and vegetable oils ensure good releasing properties.

Total Fatty Acids, % Min 3,81

**Product Application:**

1. Releasing agent used during manufacture of cement spun pipes.
2. Steel moulds used in the manufacture of kerbstones, railway sleepers, interlocking road-stones, pre-casting, screen-blocks, rainwater channels, air vents, etc.

Experienced personnel from our Technical Division are available for discussion on all aspects, especially in those difficult situations where a special formulation may be required. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 25/03/2001	Supersedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: