



Specialists in Industrial & Automotive Oil

Viscol cc	P.O. Box 7182, Centurion, 0046	Tel: (012) 661-9888
Reg No: 1987/028096/23	130 Sarel Baard Crescent	Fax: (012) 661-9882
Vat Reg : 4380103046	Gateway Industrial Park	E-mail: viscol@iafrica.com
	Rooihuiskraal	Website: www.viscol.co.za

Document Number:

TDS013

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with SABS ISO 9001 & 14001)

VISCOL SHUTTERSTRIP B

Product Description:

A low viscosity solution of highly refined petroleum and waxy based products. Besides good releasing properties, this product protects wood and hardboard shutters, prevents rusting and cement build-up on steel shutters. Adverse weather conditions does little to wash off or drying out.

Product Application:

1. Wood, hardwood and steel shuttering used when constructing columns, beams and decking, etc.
2. Conservative usage of every three to four instances.
3. For steel shutters where concrete is vibrated, apply every second time.
4. Apply to scaffolding, pumps and other equipment as a layer protector.

Product Packaging:

20 litre and 210 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects, especially in those difficult situations where a special formulation may be required. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

Page: 1/1	Date: 22/06/2000	Supersedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by: Authorised by: