

**Specialists in Industrial & Automotive Oil**

Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document Number:

TDS024**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with SABS ISO 9001 & 14001)***VISCOL BRAKE FLUID****Description & Characteristics:**

Viscol Brake Fluid is an extra heavy duty fluid which is recommended for all transport vehicles, all disk and drum brakes. Viscol Brake Fluid is a high boiling brake and clutch fluid of minimum boiling point 260 deg C, meeting SAE J1703 and United States Federal Motor Vehicle Safety Standard No116 Dot 4.

Physical Properties:

VISCOL BRAKE FLUID	
Density @ 20°C	1,04 KG/L
Flash Point (°C)	145

Packaging:

210 litre drums
20 litre drums

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use. The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 13/06/2000	Supercedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: