

**Specialists in Industrial & Automotive Oil**

Viscol cc
 Reg No: 1987/028096/23
 Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
 130 Sarel Baard Crescent
 Gateway Industrial Park
 Rooihuiskraal

Tel: (012) 661-9888
 Fax: (012) 661-9882
 E-mail: viscol@iafrica.com
 Website: www.viscol.co.za

Document
 Number:

TDS025**SUBJECT: OIL SPECIFICATIONS**

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with SABS ISO 9001 & 14001)

VISCOL GL4 80W90 AUTOMOTIVE GEAR OIL**Description & Characteristics:**

This is a premium quality gear lubricant specially recommended for synchromesh gearboxes. It contains sulphur-phosphorus EP and other additives exceeding the requirements of the U.S. Military Specifications MIL-L-2105D.

VISCOL 80W90 AUTOMOTIVE GEAR OIL	
Viscosity @ 40°C(cSt)	130
Viscosity @ 100°C(cSt)	13,9
Viscosity Index	95
Flash Point(°C)	164
Pour Point(°C)	-35

Performance Level:

API Service Classification GL-4
 MIL-L-2105
 Approved by Ford, Volkswagen and Zf
 Daimler-Benz (SAE 80W)

Benefits:

1. Full protection to transmissions with bronze components.
2. Excellent low temperature fluidity.
3. Easy gear change.
4. Major equipment Builder acceptance.

Applications:

Suitable for transmission/axle combinations synchromesh gearboxes and other applications which require a relatively low level of EP additives.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his own use.

Page: 1/1	Date: 03/05/2000	Supersedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by: Authorised by: