

**Specialists in Industrial & Automotive Oil**

Viscol cc  
 Reg No: 1987/028096/23  
 Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046  
 130 Sarel Baard Crescent  
 Gateway Industrial Park  
 Rooihuiskraal

Tel: (012) 661-9888  
 Fax: (012) 661-9882  
 E-mail: viscol@iafrica.com  
 Website: www.viscol.co.za

Document Number:

**TDS026B****SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with SABS ISO 9001 & 14001)***VISCOL GL5 85W90 AUTOMOTIVE GEAR OIL****Description & Characteristics:**

This is a premium quality gear lubricant specially recommended for synchromesh gearboxes. It contains sulphur-phosphorus EP and other additives exceeding the requirements of the U.S. Military Specifications MIL-L-2105D.

VISCOL 85W90 AUTOMOTIVE GEAR OIL	
Viscosity @ 40°C (cSt)	200
Viscosity @ 100°C (cSt)	18.2
Viscosity Index	98
Flash Point(°C)	184
Pour Point(°C)	-15

**Performance Level:**

API Service Classification GL-5.  
 MIL-L-2105D  
 Approved by Ford, Volkswagen and Zf  
 Daimler-Benz 235.1  
 MAN 342N

**Benefits:**

1. Full protection to transmissions with bronze components.
2. Excellent low temperature fluidity.
3. Easy gear change.
4. Major equipment Builder acceptance.

**Applications:**

Suitable for transmission/axle combinations synchromesh gearboxes and other applications which require a relatively low level of EP additives.

**Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.**

Page: 1/1	Date: 11/12/2000	Supercedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by: Authorised by: