

**Specialists in Industrial & Automotive Oil**Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
RooihuiskraalTel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document Number:

TDS033**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with SABS ISO 9001 & 14001)***VISCOL SUPER OUTBOARD TWOSTROKE OIL****Description**

Viscol Super Outboard Oil is a high quality ashless lubricant specially formulated for high performance water-cooled two stroke engines. It is readily miscible with fuel and contains selected additives to give good piston cleanliness, thermal stability, anti-wear and corrosion protection performance. It has been designed for use at fuel/oil ratios of up to 50:1 or lower dilution as specified by the manufacturer.

Specifications

Density @ 20°C	0,866
Viscosity cSt @ 40°C	32.0
Viscosity cSt @ 100°C	6.1
Viscosity Index	136
Flash Point (COC)°C	75
Pour Point (°C)	-15
Sulphated Ash %	0
Self-Mixing	Yes
Base	Mineral

Application

Viscol Super Outboard Oil is suitable for use in all large outboards demanding NMMA TC-W3 approved grades.

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his own use.

Page: 1/1	Date: 23/09/2000	Supercedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: