

**Specialists in Industrial & Automotive Oil**

Viscol cc  
 Reg No: 1987/028096/23  
 Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046  
 130 Sarel Baard Crescent  
 Gateway Industrial Park  
 Rooihuiskraal

Tel: (012) 661-9888  
 Fax: (012) 661-9882  
 E-mail: viscol@iafrica.com  
 Website: www.viscol.co.za

Document  
 Number:

**TDS035****SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with SABS ISO 9001 & 14001)*

**VISCOL TURBINE OILS****Description & Characteristics:**

Viscol Turbine Oils are highly refined, high viscosity index, paraffinic base oils incorporating additives to prevent rust, foaming, oxidation and wear.

**Typical Physical Properties**

ISO GRADE	32	46	68
Density @150°C	0,864	0,868	0,872
Viscosity cSt @40°C	32	46	68
Viscosity @100°C	5,45	6,87	8,79
Viscosity Index	105	104	101
Flash Point (COC) °C	217	228	246
Pour Point °C	-9	-9	-9
Demulsification Number . . .secs	60	60	90
ASTM Rust Test	Pass	Pass	Pass

**Specifications:**

Viscol Turbine Oils meet the following:

S.A.B.S. - CKS 26 Specification

DIN 51515 TD-L

British Standards BSS 489

British Admiralty OM100

Page: 1/2	Date: 01/09/10	Supersedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by: Authorised by:



**Specialists in Industrial & Automotive Oil**

Viscol cc  
Reg No: 1987/028096/23  
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046  
130 Sarel Baard Crescent  
Gateway Industrial Park  
Rooihuiskraal

Tel: (012) 661-9888  
Fax: (012) 661-9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za

Document  
Number:

**TDS035**

**SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with SABS ISO 9001 & 14001)*

**Performance Benefits:**

The high quality of the oil gives it long service life having exceptional water separation characteristics. The additives incorporated in the oil ensure rust protection in wet systems; foaming resistance and the ability to release entrained air.

**Applications:**

Viscol Turbine Oils are used in steam, gas and hydraulic turbines. They may also be used for compressors, gears, and other circulating systems where turbine quality is called for. These oils can be used in systems where silver plated components are present.

**Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his/her own use.**

Page: 2/2	Date: 01/09/10	Supersedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: