

**Specialists in Industrial & Automotive Oil**

Viscol cc
 Reg No: 1987/028096/23
 Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
 130 Sarel Baard Crescent
 Gateway Industrial Park
 Rooihuiskraal

Tel: (012) 661-9888
 Fax: (012) 661-9882
 E-mail: viscol@iafrica.com
 Website: www.viscol.co.za

Document
 Number:

TDS048

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL
(in accordance with SABS ISO 9001 & 14001)

VISCOL FORESTCUT 500 V CUTTERBAR LUBE

Description and Characteristics:

Forestcut 500 has been developed for the lubrication of chain saw cutter bars. The correct viscosity ensures maximum film strength and flow characteristics are acceptable. A tackifier is used to minimise oil throw at very high chain speeds, EP additives minimise wear.

Typical Physical Characteristics:

Viscosity cSt @ 40°C	100 - 150
Flash Point PMCC °C	252
Pour Point °C	-18
Specific Gravity	0.897

Application:

Cutterbar lube performs an entirely different task to 2-stroke oils and therefore must **NOT** be put into the engine. In a chain saw, the chain is driven by the engine and travels at high speeds around a backing plate called the cutter bar. Pegs attached to the chain fit into a groove in the cutter bar. Forestcut 500 is placed into a tank contained in the main body of the saw. An engine driven pump supplies oil into the groove to lubricate the pegs/groove interface.

Advantages & Benefits:

- Good lubrication properties
- Excellent flow characteristics
- Minimum oil thrown
- Minimised wear

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his/her own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 25/10/2004	Supercedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by:
		Authorised by: