

**Specialists in Industrial & Automotive Oil**

Viscol cc	P.O. Box 7182, Centurion, 0046	Tel: (012) 661-9888
Reg No: 1987/028096/23	130 Sarel Baard Crescent	Fax: (012) 661-9882
Vat Reg : 4380103046	Gateway Industrial Park	E-mail: viscol@iafrica.com
	Rooihuiskraal	Website: www.viscol.co.za

Document Number:

TDS054**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with SABS ISO 9001 & 14001)***VISCOL 13G GRAPHITE GREASE****Description**

Viscol 13G Graphite Grease is a smooth grey/black, lime base grease containing 15% of high quality fine graphite. Viscol 13G Graphite Grease is NLGI No 3 grease. It is water repellent and suitable for services at high temperatures where the grease acts as a carrier for the solid lubricant.

Application

Viscol 13G is recommended for rough plain bearings, slides and other parts, e.g. oven conveyor chains, gears and bearings of boiler soot-blowers, axle lubrication of trolleys operating in high temperature kilns and on the skates of pantographs of electrical locomotives and trolley buses.

Benefits

- water repellent
- good protective lubricating qualities

Physical Characteristics

NLGI No.	3
Worked Penetration @ 25°C	235/265
Drop Point, °C min	90
Oil Viscosity @ 40°C cSt	150
Colour, visual	grey/black

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the user's responsibility to determine the suitability for his own use.

Page: 1/1	Date: 01/09/10	Supersedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by: Authorised by: