

**Specialists in Industrial & Automotive Oil**Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
RooihuiskraalTel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document Number:

TDS099**SUBJECT: OIL SPECIFICATIONS****ENVIRONMENTAL & QUALITY MANUAL**
*(in accordance with SABS ISO 9001 & 14001)***VISCOAT**

Viscoat is a wood preservative, blended of hydrocarbon waxy oil. It is similar to wood preservatives used in the timber industry.

This product leaves a wax film with much of it penetrating into the epidermis of ply woods, laminated woods and such like products.

It prevents water penetration and reduces fungi.

SPECIFICATION	UNITS	LIMITS	TYPICAL
Flashpoint @ 101.325kPa	°C	55 min	77
Pour Point	°C	60 max	33
Density @ 20 °C	kg/l		0.894
Wax content	mass %		5
Water content	mass %	0.3 max	0.1
Viscosity @100 °C	cSt	12 max	7

Experienced personnel from our Technical Division are available for discussion on all aspects. Recommendations are given in good faith but without warranty. It is the users responsibility to determine the suitability for his own use.

The products discussed are sold without any warranties either expressed or implied, including warranties of merchantability and of fitness for particular purpose.

Page: 1/1	Date: 01/09/10	Supersedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: