



**Specialists in Industrial & Automotive Oil**

Viscol cc  
Reg No: 1987/028096/23  
Vat Reg : 4380103046

P.O. Box: 7182, Centurion, 0046  
130 Sarel Baard Crescent  
Gateway Industrial Park  
Rooihuiskraal

Tel: (012) 661-9888  
Fax: (012) 661-9882  
E-mail: viscol@iafrica.com  
Website: www.viscol.co.za

Document  
Number:

**TDS110**

**SUBJECT: OIL SPECIFICATIONS**

**ENVIRONMENTAL & QUALITY MANUAL**  
*(in accordance with SABS ISO 9001 & 14001)*

**LITHIUM EP 2 GREASE**

**Description** : **LITHIUM EP 2 GREASE** is high quality multi purpose Lithium base grease blended from solvent refined oils and incorporates multi functional extreme pressure additives as well as corrosion and oxidation inhibitors. It is suitable for operating temperatures between -30°C and 130°C.

**Specifications** : **LITHIUM EP 2 GREASE** conforms to SBSA specification 1014.

**Application** : **LITHIUM EP 2 GREASE** are designed for use in highly loaded plain and roller bearings as well as for shock loading conditions in steel mills. It is suitable for use in the full range of bearing speeds encountered in electric motors, machines and wood working tools, production equipment. Textile and paper making industry, generators and all types of vehicles. The smooth consistency makes these greases ideal for use in centralized lubrications systems and they can be used on ferrous on non-ferrous metals.

**Characteristics** :

Thickening Agent	Lithium
NLGI Classification	2
Work Penetration at 25°C	265 – 295
Drop point °C	180
Timken OK load Kg	33
Oil Viscosity at 40° C	200
Recommended Temp Range	-30° to 130°C
Water washout	5%

Page: 1/1	Date: 01/09/10	Supersedes: New	
SOP ref: New	Compiled by: Alex Hime	Checked by:	Authorised by: