



Specialists in Industrial & Automotive Oil

Viscol cc
Reg No: 1987/028096/23
Vat Reg : 4380103046

P.O. Box 7182, Centurion, 0046
130 Sarel Baard Crescent
Gateway Industrial Park
Rooihuiskraal

Tel: (012) 661-9888
Fax: (012) 661-9882
E-mail: viscol@iafrica.com
Website: www.viscol.co.za

Document
Number:

TDS116

SUBJECT: OIL SPECIFICATIONS

ENVIRONMENTAL & QUALITY MANUAL

(in accordance with SABS ISO 9001 & 14001)

LITHIUM NO 2 & NO 3 GREASE

Description : **LITHIUM NO 2 & NO 3 GREASE** are high quality greases blended with solvent refined base oils, suitable for operating temperature between -30° and 130°C. They are resistant to water and steam and are multipurpose greases containing oxidation and corrosion inhibitors.

Application : The lubrication of plain, needle, ball and roller bearings. They can be used with ferrous and non ferrous metals, sealing materials and most dispensing equipment

Characteristics :

Thickening Agent	Lithium	Lithium
NLGI Classification	2	3
OIL / Pool @ 40°C	200 cst	80 cst
Drop Point	>180°	>180°
Unworked penetration	280	235
Temperature Range	-30°C to 130°C	30°C to 130°C

Page: 1/1	Date: 01/09/10	Supercedes: New
SOP ref: New	Compiled by: Alex Hime	Checked by:
		Authorised by: